

CNC ROUTER MACHINES





STORMA ENGRAVER R3/ TECHNIC R5

PRODUCT LINE

Usel Makina's CNC milling machines are employed across diverse industries, such as woodworking, stoneworking, machinery, instrumentation, and metalworking. Our machines offer several benefits, including superior reliability, exceptional positioning accuracy, and rapid engraving speed. The advanced CNC controller guarantees minimum processing time and reduced costs.



ELIPTIC CUTS

2

STORMA ENGRAVER R3-2212

3-AXIS MONOBLOCK CNC ROUTER MACHINE

This machine offers high-quality components, reliability, ease of operation, and broad functionality at an affordable price, making it an ideal solution for small and medium-sized production.

The sturdy and stable design, free from vibrations and reinforced with a strong profile, enables high-quality milling and engraving tasks on a broad range of materials in both 2D and 3D.







Monoblock body and rigid construction. Does not need to be mounted



Automatic programming and transfer of CAD files via USB



Wide range of options for expanding functionality



Multifunctional mobile operator panel for full control



TEX PowerD high performance CNC module provides 3-axis operation control



STORMA TECHNIC R5-3020

5-AXIS MONOBLOCK CNC ROUTER MACHINE

The flagship machine of the series enables high-quality machining, milling, and engraving of complex materials with its 5 interpolated axes, reinforced profile, and vibration-free design. Additionally, the machine offers a wide range of options, providing limitless possibilities.





Head rotation 0-360° (axis C)

Cutting Head can rotate 360° clockwise uninterrupted can make circular and diagonal cutting with interpolation of X,Y,C axises together. C axis is thrusted with (<1') Reduction gear servomotor (Interpolation with Z axis also)



Inclination of head 0-90° (axis A)

CNC controlled 5.axis is thrusted with (<1') Reduction gear – servomotor Milling head rotate 0-90 with CNC controlled and can make and can make all milling profile with interpolating of X,Y,C,Z,A axes.



OPTION

11" Panel CNC Unit

CNC Unit with 11" Display. Automatic programming and transfer of CAD files to the operator panel via USB Multi-functional (15 operator friendly controls) Mobile Operator Panel.

Monoblock body and rigid construction. Does not need to be mounted

Multifunctional mobile operator

panel for full control

ſ	يت التر
l	

Automatic programming and transfer of CAD files via USB



TEX PowerD high performance CNC module provides 5-axis operation control

CONTROL AND SOFTWARE

Hand Type Operator Panel

Digital display to control and positioning of the X,Y,Z axes. Automatic programming. Multi functional (15 operator friendly control) axis joystick / feed-rate / rpm adjusting -Blade current (Ampere) can be seen on mobile operator panel

3/5-axis CNC control unit TEX

OPTION



DDX Easystone CAM software Basic

EasySTONE is a powerful, simple and intuitive CAD/ automated control system software adapted for STORMA machines and designed for the stone processing industry. Allows you to manage all aspects related to CNC machining.

MACHINE BODY

Construction


Bridge type machine. Monoblock, rigid (body), non vibrational construction. Heavy and reinforced. No need mounting

Complete Heat treatment and fully bohrwerked chasis:

- Heat treatment has been applied to all steel parts after welding to prevent residual stresses and processed in Bohrwerk.

- On the machined surface, two sides of linear rails (guides) are mounted

To provide high rust resistance, 2 lines zinc based undercoat and 2 lines acrilic painting.



Fixed Table 2200×1200 mm (Optional up to 4000×12000)

FINISHED PRODUCTS



FUNEARY ART

BAS-RELIEFS

VANITY TOP

KITCHEN TOP

OPTIONS



TURNING - LATHE



AUTOMATIC TOOL CHANGER and Spindle (20 tools)



Stone Thickness Measuring System



2nd Head of Copy on single Z axis



Milling tools



Complete Hot Galvanised Coating

TECHNICAL SPECIFICATIONS

★ {´◯↓ Lathe (option)

Storma Engraver R3-2212

Storma Technic R5-3020

Max. number of interpolated axes	3+1*	5+1*
Cut Head movement (X), mm	2200 - 8000	2200 - 8000
Bridge Cross Travel (Y), mm	1200 - 4000	1200 - 4000
Vertical Travel (Z), mm	300 - 500	300 - 500
Head rotation (C axis)	—	0-360°
Head tilting (A axis)	—	0-90°
Travel Speed (X,Y), m/min	0-30	0-30
Spindle power, kW	5,5 (opt. up to 11 kW)	5,5 (opt. up to 11 kW)
Spindle speed, rpm	12000-24000	12000-24000
Operating Voltage, V	380 / 50	380 / 50
Machine Dimensions (LxWxH), mm	3850 × 1900 × 2400	4750 × 2750 × 2750
Machine weight. kg	4 000	5 600

PROCESSING GALLERY



PRODUCT RANGE



BRIDGE SAWS

5-AXIS CNC MACHINING CENTERS



WHY US?



25 YEARS OF SUCCESS IN THE MARKET WE HAVE BEEN CHOSEN BY 260 COMPANIES FROM 25+ COUNTRIES HIGHEST MANUFACTURING STANDARDS UNIQUE PRECISION PROCESSING TECHNOLOGY EUROPEAN QUALITY AT A REASONABLE PRICE





- https://uselmakina.ru/
- **+**90 216 526 45 75
- o usel@usel.com.tr



İMES Sanayi Sitesi A Blok 104. Sok. No 5 Y.Dudullu 34776 Ümraniye / İstanbul

